MATERIAL SAFETY DATA SHEET

Page 1 of 3

Chartpak, Inc. One River Road Leeds, MA 01053 Phone: 413-584-5446 or 800-628-1910

Emergency Medical Number: 888-786-0972

Creation Date: January 18, 2008

Section One:	Product Inform	mation			
Product Name:	Max Grumbacher Artists' O	il Color			
Product Sizes:	7.5, 24, 37, and 150 ml				
Product Class:	Artists' Oil Color				
Section Two:	Ingredients				
Ingredients		CAS Number	% by Weight	PEL/TLV	
Linseed Oil		8001-26-1	62.0%	N/A	
Cobalt Pigment		N/A	58.0%	N/A	
Barium Sulfate		7727-43-7	15.0%	10 mg/m3	

Section Three: Hazards Identification

WARNING: MAY BE HARMFUL IF SWALLOWED. EXPOSURE MAY CAUSE DAMAGE TO THE TESTES, OR DAMAGE TO THE HEART.

CONTAINS: SOLUBLE COBALT.

KEEP OUT OF REACH OF CHILDREN.

**WARNING: This product contains lead, a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. **WARNING: This product contains an additional chemical known to the State of California to cause cancer.

Section Four:	First Aid Measures
Inhalation:	Move to fresh air.
Skin Contact:	Wash with soap and water.
Eye Contact:	Flush with flowing water.
Ingestion:	If swallowed, get prompt medical attention. For further health information, contact a poison control center.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: M040

MATERIAL SAFETY DATA SHEET

MSDS #: M040

Page 2 of 3

Section Five: F	ire Fighting Measures
Flash Point:	Not flammable
Flammability Limits (% by volume	e): Lower: Not explosive Upper: Not explosive
Extinguishing Media:	As appropriate for surrounding area.
Special Fire Fighting Measures:	No special fire fighting procedures.
Unusual Fire and Explosion Hazards:	Not combustible

Section Six:	Accidental Release Measures
--------------	-----------------------------

No special spill procedures required

Other Protective Equipment (Gloves, Goggles, Etc.):

None

Section Seven:	Handling and Storage
Handling:	When using, do not eat, drink, or smoke.
Storage:	KEEP OUT OF REACH OF CHILDREN.
Section Eight:	Exposure Controls and Personal Protection
Respiratory Prote Special Ventilation	

Work/Hygiene Practices:	PRECAUTIONS: Wash hands immediately after use. When using, do not eat, drink, or smoke.	
	KEEP OUT OF REACH OF CHILDREN.	

Section Nine:	Physical and Chemical Proper	rties		
Boiling Point: No	lot determined	Melting Point:	Not determined	
Vapor Pressure: No	lot determined	Specific Gravity:	Not determined	
Specific Vapor Density (AIR =	= 1): Not determined	Evaporation Rate (Buty	Acetate = 1): Not o	determined
Solubility in Water: No	lot determined	Reactivity in Water:	Non-reactive	
Appearance and Odor: Co	colored paints; oily odor			

Section Ten:	Stability and Reactivity	
Stability:	Stable	
Conditions to Avoid:	Excessive heat	
Chemical Incompatibility:	None known	
Hazardous Decomposition:	None known	
Hazardous Polymerization:	Will not occur	

MATERIAL SAFETY DATA SHEET

MSDS #: M040

Page 3 of 3

Section Eleven:	Toxicological Information	
IARC Monographs:	No	
National Toxicology P	rogram: No	
OSHA Regulated:	No	
Effects/Symptoms of Acute Exposure:	May be harmful if swallowed.	
Effects/Symptoms of Chronic Exposure:	Prolonged exposure may cause damage to the heart and testes.	
Medical Conditions Us Aggravated By Overes of This Product:		
Section Twelve:	Ecological Information	
Not available		
Section Thirteen:	Disposal Considerations	
Dispose in accordance	e with Federal, State, and Local Regulations.	
Section Fourteen:	Transport Information	

Not regulated as a hazardous material by DOT, IMO, or IATA.

Section Fifteen:	Regulatory Information

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

Section Sixteen:	Other Information
HMIS Code	
Health 1	Chartpak, Inc. is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling
Flammability 0	standard ASTM D4236 and is labeled with the AP Seal. Products bearing the AP Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for
Reactivity 0	any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236.
Personal Protection N/A	

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.